## **Historical Specification**

**Auxiliary High Flow** 

To find historical specifications for discontinued equipment, select the product category, model number and first year of production. For additional information, visit the service and maintenance section or contact your local dealer.

Family			Model	First year of production		
S	kid-Steer Loade	ers	Bobcat S185	2005		
Standard	Optional	Not Applicable			Units	US
				Bobcat \$185		
Engine						
Emissions Tier	(EPA)			Tier 2		
Engine Cooling				Liquid		
Engine Fuel				Diesel		
Horsepower				59 hp		
Turbocharged E	ingine					
Perform	ance					
Rated Operating	Capacity (SAE	)		1,850 lb		
Tipping Load				4076 lb		
Operating Weig	ht			6220 lb		
Travel Speed				7.3 mph		
Travel Speed (2	-speed option)			11.1 mph		
Capaciti	ies					
Fuel Tank				24 gal		
Hydrauli	ic System					
System Relief @		rs .		3,300 psi		
Auxiliary Std Flow				16.9 gal/min		

26.4 gal/min

## **Dimension**

Length	101.8 in
Length without Attachment	101.8 in
Length with Standard Bucket	130.3 in
Width	66 in
Width (with bucket)	68 in
Height	76.3 in
Height with Operator Cab	76.3 in
Height to Bucket Hinge Pin	118.2 in
Reach @ Maximum Height	29.6 in
Turning Radius	78.8 in
Wheelbase	40.6 in

## **Features**

Joystick Control

Air Conditioning

Adjustable Seat

BICS System (Interlock)

Cab Enclosure

Sound Option

Cab Heater

Rear Window

Lift-Arm Support

Suspension Seat

Two Speed Travel

Deluxe Instrumentation

Engine Shutdown

Hydraulic Bucket Positioning

High Flow Option

Auxiliary Hydraulics

Bob-Tach Attachment System

Power Bob-Tach

Ride Control

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.