## **Historical Specification**

To find historical specifications for discontinued equipment, select the product category, model number and first year of production. For additional information, visit the service and maintenance section or contact your local dealer.

Family Com	pact Track Loa		odel  Bobcat T190	First year of production 2005	
Out	paot Haok Loa		Bobout 1130	2000	
Standard	Optional	Not Applicable			<b>Units</b> US
				Bobcat T190	
Engine					
Emissions Tier (	EPA)			Tier 2	
Engine Cooling				Liquid	
Engine Fuel				Diesel	
Horsepower				66 hp	
Turbocharged E	ngine				
Performa	ance				
Rated Operating	Capacity (SAE	E)		1,900 lb	
Operating Capac	city (50% of Tip	))		3426 lb	
Tipping Load				6851 lb	
Operating Weigh	nt			7612 lb	
Travel Speed				7.1 mph	
Ground Pressure	e (Rubber)			4.9 psi	
Capacitio	es				
Fuel Tank				28 gal	
Hydrauli	c System				
System Relief @	Quick Coupler	rs		3,250 psi	
Auxiliary Std Flo	w			16.3 gal/min	
Auxiliary High Fl	ow			25.5 gal/min	

## **Dimension**

Length	101.8 in
Length without Attachment	101.8 in
Length with Standard Bucket	130.3 in
Width	66 in
Height	76.3 in
Height with Operator Cab	76.3 in
Height to Bucket Hinge Pin	118.2 in
Reach @ Maximum Height	30.9 in
Turning Radius	78.8 in
Length of track on ground	55.2 in
Track Width	12.6 in
Track Width - Optional	16 in

## **Features**

Joystick Control

Air Conditioning

BICS System (Interlock)

Cab Heater

Operating Lights

Suspension Seat

Two Speed Travel

Deluxe Instrumentation

Engine Shutdown

Hydraulic Bucket Positioning

High Flow Option

Auxiliary Hydraulics

Bob-Tach Attachment System

Power Bob-Tach

Ride Control

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.